



MAGNETIC/STEREO OUTPUT-

WHEN USED WITH A MONO CABLE, THIS OUTPUT PROVIDES A PASSIVE SIGNAL FROM THE MAGNETIC PICKUPS ONLY.
WHEN USED WITH A STEREO (TRS) CABLE, TIP OUTPUTS PASSIVE MAGNETIC SIGNAL; RING OUTPUTS BUFFERED PIEZO SIGNAL.

PIEZO/MONO OUTPUT-

USE MONO CABLE ONLY.
WHEN ONLY THIS JACK IS CONNECTED, A BUFFERED AND MIXED COMBINATION OF THE MAGNETIC AND PIEZO SIGNALS IS PRODUCED.
WHEN BOTH JACKS ARE USED, THIS OUTPUT WILL PRODUCE THE BUFFERED PIEZO SIGNAL ONLY; THE MAGNETIC SIGNAL IS DIVERTED TO THE MAGNETIC/STEREO OUTPUT.

ERNIE BALL / MUSIC MAN

AXIS SPORT GUITAR PIEZO/HH
CONTROL FUNCTION DIAGRAM

REV	DRAWN BY HFL	APPROVED BY DDG	DATE 7-7-99
SCALE NONE	TOLERANCE N/A	PART NO.	